



Shanghai Yunqing Industrial Co., Ltd.

No.508, Fengyong Road, Fengxian District, Shanghai, China  
Email: [yichita@yqgroup.vip](mailto:yichita@yqgroup.vip)

**CAUTION:** The straps on the respirator are completely latex-free. Individuals who are highly sensitive to natural rubber latex can feel free to use.

**DONNING & FITTING INSTRUCTIONS:**

Follow these instructions each time respirator is worn.

- 1. Cup respirator in one hand with nosepiece at fingertips, allow headbands to hang freely below hand.
- 2. Hold respirator under chin, with nosepiece up.
- 3. Locate the upper strap across the crown of the head and the lower strap below the ears. Straps must not be twisted.
- 4. Using both hands, mold nose clip to the shape of the nose to ensure a close fit and good seal. Pinching the nose clip using only one hand may result in less effective respirator performance. Use two hands perform seal check prior to each wearing. To check fit, place both hands completely over the respirator and exhale. Be careful not to disturb the position of the respirator.

If air leaks around nose, readjust the nosepiece as described in step. If air leaks at the respirator edges, work the straps back along the sides of your head. If you CANNOT achieve a proper fit, DO NOT enter the contaminated area. See your supervisor.

**FIT-CHECK THE FACE-SEAL AS FOLLOWS:**

- Place both hands over the respirator – do not disturb the position of the respirator.
- Inhale sharply (you should feel a negative pressure inside the respirator).
- If you detect air leak, re-adjust the head straps and/or the nose piece.

The respirator must be used in accordance with OSHA regulations 29 CFR 1910.134 which includes the requirement for fit testing

before use.

**WARNING:** If you cannot achieve satisfactory fit, do NOT enter the contaminated area. See your Supervisor or contact us via email at: [yichita@yqgroup.vip](mailto:yichita@yqgroup.vip).

**USE INSTRUCTIONS:**

- 1. Failure to follow all instructions and limitations on the use of this respirator and/or failure to wear this respirator during all times of exposure can reduce respirator effectiveness and may result in sickness or death.
- 2. Before occupational use of this respirator, a written respiratory protection program must be implemented meeting all local government requirements. In the U.S., employers must comply with OSHA 29 CFR 1910.134 which covers medical evaluation, training, and fit testing.
- 3. Particles that can be dangerous to your health include those not visible to your eyes.
- 4. Leave the contaminated area immediately and contact supervisor if dizziness, irritation, or other distress occur.
- 5. Store the respirator away from contaminated areas when not in use.
- 6. Dispose of used product in accordance with applicable regulations.
- 7. Inspect the respirator prior to each use to assure that it is in good operation condition. Examine all the respirator parts for signs of damage including two head straps with their welding spots, noseclip, and nosefoam. The respirator should be disposed of immediately upon observation of damaged or missing parts. Filtering facepieces are to be inspected prior to each use to assure there are no holes in the breathing zone and no damage has occurred. Holes resulting from ripped or torn filter material around strap welding spots are considered damage. Immediately replace respirator if damaged.

**USE LIMITATIONS:**

- 1. Do NOT use the respirator and enter or stay in a contaminated area under the following circumstances:
  - atmosphere contains less than 19.5% oxygen.
  - atmosphere contains oil aerosols.
  - for protection against gases or vapors.
  - contaminants or their concentrations are unknown or immediately dangerous to life or health.
  - for sandblasting, paint-spray operations, asbestos.
- 2. Do NOT modify or misuse the respirator.
- 3. Do NOT use the respirator with beards or other facial hair that interferes with direct contact between the face and the edge of the

respirator, or any other conditions that may prevent a good face-seal.



Shanghai Yunqing Industrial Co., Ltd.

No.508, Fengyong Road, Fengxian District, Shanghai, China 201414

Email: [yichita@yqgroup.vip](mailto:yichita@yqgroup.vip)

THIS RESPIRATOR IS APPROVED ONLY IN THE FOLLOWING CONFIGURATION:

TC-	Protection <sup>1</sup>	Respirator	Cautions and Limitations <sup>2</sup>
84A-9384	N95	YQD95V	ABCJMNOP

**1. Protection**

N95 - Particulate Filter (95% filter efficiency level)  
Effective against particulate aerosols free of oil;  
time use restrictions may apply

**2. Cautions and Limitations**

- A - Not for use in atmospheres containing less than 19.5% oxygen.
- B - Not for use in atmospheres immediately dangerous to life or health.
- C - Do not exceed maximum use concentrations established by regulatory standards.
- J - Failure to properly use and maintain this product could result in injury or death.
- M - All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA and other applicable regulations.
- N - Never substitute, modify, add, or omit parts. Use only exact replacement parts in the configuration as specified by the manufacturer.
- O - Refer to User Instructions, and/or maintenance manuals for information on use and maintenance of these respirators.
- P - NIOSH does not evaluate respirators for use as surgical masks.

**WARNING:** This respirator helps protect against certain contaminants. It may not eliminate the risk of contracting disease or infection. **Misuse may result in sickness or death.** Materials which may come into contact with the wearer’s skin could cause allergic reactions to susceptible individuals.

FOR MORE INFORMATION or assistance, please contact Shanghai Yunqing Industrial Co., Ltd.