



Shanghai Yunqing Industrial Co., Ltd.
www.yqgroup.vip

YQD960/YQD960B N95 Particulate Respirator

Use Instructions

IMPORTANT: Keep Use Instructions for reference

WARNING

This respirator helps protect against certain contaminants. It may not eliminate the risk of contracting disease or infection. **Misuse may result in sickness or death.** Materials which may come into contact with the wearer's skin could cause allergic reactions to susceptible individuals.

USE INSTRUCTIONS:

1. Failure to follow all instructions and limitations on the use of this respirator and/or failure to wear this respirator during all times of exposure can reduce respirator effectiveness and may result in sickness or death.
2. Before occupational use of this respirator, a written respiratory protection program must be implemented meeting all the local government requirements. In the United States, employers must comply with OSHA 29 CFR 1910.134 which includes medical evaluation, training, and fit testing.
3. The particles which can be dangerous to your health include those so small that you cannot see them.
4. Leave the contaminated area immediately and contact supervisor if dizziness, irritation, or other distress occurs.
5. Store the respirator away from contaminated areas when not in use.
6. Dispose of used product in accordance with applicable regulations.
7. Inspect the respirator prior to each use to assure that it is in good operation condition. Examine all the respirator parts for signs of damage including two head straps with their welding spots, noseclip. The respirator should be disposed of immediately upon observation of damaged or missing parts. Filtering facepieces are to be inspected prior to each use to assure there are no holes in the breathing zone and no damage has occurred. Holes resulting from ripped or torn filter material around strap welding spots are considered damage. Immediately replace respirator if damaged.

Storage Conditions and Shelf Life:

Before use, store respirators in the original packaging, away from contaminated areas, dust, sunlight, extreme temperatures, excessive moisture, and damaging chemicals. When stored in original packaging between temperatures from -20°C to +38°C and not exceeding 80% RH, the product may be used until the Best Before Date (BBD) specified on packaging.



DONNING & FITTING INSTRUCTIONS:

1. Cup respirator in one hand with noseclip at fingertips, allow headbands to hang freely below hand.
2. Hold respirator under chin, with noseclip up.
3. Locate the upper strap across the crown of the head and the lower strap below the ears. Straps must not be twisted.
4. Using both hands, mold nose clip to the shape of the nose to ensure a close fit and good seal. Pinching the nose clip using only one hand may result in less effective respirator performance. Use two hands perform seal check prior to each wearing. To check fit, place both hands completely over the respirator and exhale. Be careful not to disturb the position of the respirator.
If air leaks around nose, readjust the noseclip as described in step. If air leaks at the respirator edges, work the straps back along the sides of your head. If you CANNOT achieve a proper fit, DO NOT enter the contaminated area. See your supervisor.

FIT-CHECK THE FACE-SEAL AS FOLLOWS:

- Place both hands over the respirator – do not disturb the position of the respirator.
- Inhale sharply (you should feel a negative pressure inside the respirator).
- If you detect air leak, re-adjust the head straps and/or the nose piece.

The respirator must be used in accordance with OSHA regulations 29 CFR 1910.134 which includes the requirement for fit testing before use.

WARNING: If you cannot achieve satisfactory fit, do NOT enter the contaminated area. See your Supervisor or contact us via email [at: yichita@yqgroup.vip](mailto:yichita@yqgroup.vip).

USE LIMITATIONS:

1. Do **NOT** use the respirator and enter or stay in a contaminated area under the following circumstances:
 - atmosphere contains less than 19.5% oxygen.
 - atmosphere contains oil aerosols.
 - for protection against gases or vapors.
 - contaminants or their concentrations are unknown or immediately dangerous to life or health.
 - for sandblasting, paint-spray operations, asbestos.
2. Do **NOT** modify or misuse the respirator.
3. Do **NOT** use the respirator with beards or other facial hair that interferes with direct contact between the face and the edge of the respirator, or any other conditions that may prevent a good face-seal.



Shanghai Yunqing Industrial Co., Ltd.

No.508, Fengyong Road, Fengxian District, Shanghai, China 201414

Email: yichita@yqgroup.vip

THIS RESPIRATOR IS APPROVED ONLY IN THE FOLLOWING CONFIGURATION:

TC-	Protection ¹	Respirator		Cautions and Limitations ²
		YQD960	YQD960B	
84A-9421	N95	X	X	ABCJMNOP

1. Protection

N95 - Particulate Filter (95% filter efficiency level)
Effective against particulate aerosols free of oil;
time use restrictions may apply

2. Cautions and Limitations

- A - Not for use in atmospheres containing less than 19.5% oxygen.
- B - Not for use in atmospheres immediately dangerous to life or health.
- C - Do not exceed maximum use concentrations established by regulatory standards.
- J - Failure to properly use and maintain this product could result in injury or death.
- M - All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA and other applicable regulations.
- N - Never substitute, modify, add, or omit parts. Use only exact replacement parts in the configuration as specified by the manufacturer.
- O - Refer to User Instructions, and/or maintenance manuals for information on use and maintenance of these respirators.
- P - NIOSH does not evaluate respirators for use as surgical masks.

FOR MORE INFORMATION or assistance, please contact
Shanghai Yunqing Industrial Co., Ltd.
No.508, Fengyong Road, Fengxian District, Shanghai, China 201414
Hotline: +86 400 178 1700
Email: yichita@yqgroup.vip
www.yqgroup.vip